

24" Depth, 18" High	MODEL
<ul style="list-style-type: none"> <li>◆ 635± CFM</li> <li>◆ 7" Round Duct</li> </ul>	WH1930PSB-SS WH1936PSB-SS WH1942PSB-SS WH1948PSB-SS
<ul style="list-style-type: none"> <li>◆ 765± CFM</li> <li>◆ 8" Round Transition</li> </ul>	WH1930PSB-8-SS WH1936PSB-8-SS WH1942PSB-8-SS WH1948PSB-8-SS
<ul style="list-style-type: none"> <li>◆ 850± CFM</li> <li>◆ 10" Round Transition</li> </ul>	WH1930PSB-K-SS WH1936PSB-K-SS WH1942PSB-K-SS WH1948PSB-K-SS
<ul style="list-style-type: none"> <li>◆ 1295± CFM</li> <li>◆ Two (2) 8" Round Transitions</li> </ul>	WH1936PS1-TWB-8-SS WH1942PS1-TWB-8-SS WH1948PS1-TWB-8-SS WH1954PS1-TWB-8-SS WH1960PS1-TWB-8-SS
Option: Rear Vented Available. Mesh Filters Only. Ex: WH1900PSR	



**FEATURES:**

- ◆ 304 Marine Grade Stainless Steel
- ◆ Variable Controls
- ◆ Sones: 1.5 to 4.6
- ◆ Front Panel Lighting: LED Bulbs Included.
  - 30" to 48" Hoods take 2 Bulbs (1 Set)
  - 54" to 60" Hoods take 4 Bulbs (2 Sets)
- ◆ Heat Controlled Thermostat, Fire Safety Controlled. Activates at 130 degrees. (Not Available on Outdoor Series)
- ◆ Electrical: 115 AC, 60 Hz, 9 Amps. For proper installation, unit must be hard wired. Suggested use with 15 Amp Circuit.
- ◆ Suggested Distance Code: 36" above cooking surface.

**OPTIONS:**

- ◆ Duct covers made to your specifications.  
Provide Width and Height: Ex: WH-STK-HEIGHT x WIDTH
- ◆ Remote wiring, see accessories.
- ◆ Custom Sizes Available.

NO Performance Warranty over BBQ Grills/Griddles.

