## Pfister

Specifications

Job Pack Contains 12

• 1.5 GPM Aerator Available

• Stainless Steel Ball Valve

(Order 941-372 Separately)

• 10 Year Commercial Warranty

**Kitchen Faucets** 

1.8 GPM Flow Rate


• 3-Hole Installation

**Features** 

## Pfirst Series<sup>™</sup>

Single Control Kitchen Faucet

J134-144C Finish(C) J134-144S Finish(S) 🔲



- Single Control
- 3-Hole Installation

• IAPMO Certified

• ASME A112.18.1

CEC Compliant

• Cal Green Compliant

CSA B125 Certified

• Stainless Steel Ball Valve

**Code Compliance** 

Pfister products are designed and

following standards and codes:

• NSF 61/9 Annex G (Low lead)

manufactured in compliance with the

ADA Compliant-ANSI A117.1 (Lever handles only)

## رم بلج ا

Swivel Spout

8 [204] 8-1/8 [206] 6-5/16 [160] 4-23/32 [120] 圉 2-1/32 [51] 1-1/2 [38] MAX DECK THICKNESS 1/2-14 NPSM 2 PL 10 [254]

Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings

June 11, 2020

SS-J134-144